

BUILT FOR SPEED. BUILT FOR ACCURACY.



INTRODUCING **IMPULSE™**

STRAIGHT PULL BOLT ACTION DESIGN INNOVATIVE TECHNOLOGIES SAFETY FOCUSED



- 1. HEXLOCK**
a robust bolt design with bearings that expand to allow for superior safety. As gas pressure from a fired round builds, HEXLOCK™ remains engaged.



- 3. MULTI-POSITION, AMBIDEXTROUS BOLT HANDLE**
allows for multiple positions for the bolt angle, in addition to right or left hand position, and also serves as a security key to the gun.



- 2. ROBUST LOCK UP**
design with free floating, interchangeable bolt head.



- 4. INTEGRAL MIL-SPEC PICATINNY RAIL** enables reliable and sturdy mounting with multiple optic mount options.



- 5. AMBIDEXTROUS TANG SAFETY**
magazine release, and quick release allow for intuitive operation.



- 6. SINGLE STEP QUICK RELEASE** button unlocks the bolt and automatically resets, eliminating cycling failures.



- 7. SINGLE STEP SIDE BOLT**
release with no manipulation required on bolt insertion.



- 8. CYLINDRICAL BOLT**
design allows for smooth handling and prevents bolt bind.


SCAN FOR MORE ON **IMPULSE** TECHNOLOGY



**PROVEN FOUR-BOLT
BARREL CLAMP**
with inte gral lock provides easy
disassembly and repeatable zero.



**SELF-CONTAINED
MODULAR SUBASSEMBLIES**
enable simple toolless disassembly
and assembly.



ROTARY BOLT HANDLE
allows for controlled loading, leveraged
bolt close, and pre-extraction.



BARREL EXTENSION
with barrel locknut that allows for
accurate headspace control.



NEW



IMPULSE HOG HUNTER

OD Green AccuStock® with AccuFit® // AccuTrigger // Straight Pull Bolt // Matte Black Aluminum Receiver // Carbon Steel Heavy Fluted Barrel // Threaded (5/8-24") // Integral 2Ø MOA rail // Detachable Box Magazine

Length of Pull = 12.75–13.75" / 32,4 - 34,9 cm



PART #	CALIBER	BARREL LG (IN/CM)	TWIST RATE	OVERALL LG (IN/CM)	MAG CAPACITY	WEIGHT (LB/KG)	ACCU TRIGGER ADJ.
57653	.308 WIN.	18 / 45,7	10	39.3 / 99,8	4	8.5 / 3,9	2.5-6LBS / 1.130-2.270 g
57654	6.5 CREEDMOOR	20 / 50,8	8	37.3 / 94,7	4	8.5 / 3,9	2.5-6LBS / 1.130-2.270 g
57655	30-06 SPFLD.	20 / 50,8	10	41.5 / 105,4	4	8.7 / 4,0	2.5-6LBS / 1.130-2.270 g
57656	300 WIN. MAG.	24 / 61,0	10	45.5 / 115,6	3	9.3 / 4,2	2.5-6LBS / 1.130-2.270 g

NEW



IMPULSE BIG GAME

KUIU® Verde 2.0 Camo // AccuStock® with AccuFit® // AccuTrigger // Hazel Green Cerakote® Aluminum Receiver and Steel Barrel // Straight Pull Bolt // Carbon Steel Fluted Barrel // Threaded (5/8-24") // Integral 2Ø MOA rail // Detachable Box Magazine

Length of Pull = 12.75–13.75" / 32,4 - 34,9 cm



PART #	CALIBER	BARREL LG (IN/CM)	TWIST RATE	OVERALL LG (IN/CM)	MAG CAPACITY	WEIGHT (LB/KG)	ACCU TRIGGER ADJ.
57647	6.5 CREEDMOOR	22 / 55,9	8	43.5 / 110,5	4	8.8 / 4,0	2.5-6LBS / 1.130-2.270 g
57648	.243 WIN.	22 / 55,9	9.25	43.5 / 110,5	4	8.8 / 4,0	2.5-6LBS / 1.130-2.270 g
57649	.308 WIN.	22 / 55,9	10	43.5 / 110,5	4	8.8 / 4,0	2.5-6LBS / 1.130-2.270 g
57652	300 WSM	24 / 61,0	10	43.5 / 110,5	2	8.9 / 4,0	2.5-6LBS / 1.130-2.270 g
57650	30-06 SPFLD.	22 / 55,9	10	43.5 / 110,5	4	8.8 / 4,0	2.5-6LBS / 1.130-2.270 g
57651	300 WIN. MAG.	24 / 61,0	10	43.5 / 110,5	3	8.9 / 4,0	2.5-6LBS / 1.130-2.270 g

NEW



IMPULSE PREDATOR

Mossy Oak® Terra Gila Camo // AccuStock® with AccuFit® // AccuTrigger // Straight Pull Bolt // Matte Black Aluminum Receiver // Carbon Steel Medium Contour Barrel // Threaded (5/8-24") // Integral 2Ø MOA rail // Detachable AICS Magazine

Length of Pull = 12.75–13.75" / 32,4 - 34,9 cm



PART #	CALIBER	BARREL LG (IN/CM)	TWIST RATE	OVERALL LG (IN/CM)	MAG CAPACITY	WEIGHT (LB/KG)	ACCU TRIGGER ADJ.
57657	22-250 REM.	20 / 50,8	10	41.5 / 105,4	10	8.5 / 3,9	2.5-6LBS / 1.130-2.270 g
57658	.243 WIN.	20 / 50,8	9.25	41.5 / 105,4	10	8.5 / 3,9	2.5-6LBS / 1.130-2.270 g
57659	.308 WIN.	20 / 50,8	10	41.5 / 105,4	10	8.5 / 3,9	2.5-6LBS / 1.130-2.270 g
57660	6.5 CREEDMOOR	20 / 50,8	8	41.5 / 105,4	10	8.5 / 3,9	2.5-6LBS / 1.130-2.270 g